



Visonic®

For a secure way of life

GB-501 PG2

Wireless PowerG® Glass-break Detector



- Industry-leading, patented glass-break detection technology
- Acoustic Pattern Recognition Technology™ provides 360° coverage
- Maximum detection range of 6m (20ft) for plate, tampered, laminated and wired glass
- PowerG two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology - Provides robustness and reliability closer than ever to wired
- Large transmission range enabling repeater-free installations
- Battery life of 4 years with typical use
- Visible link quality indication shown on the device reduces installation time
- Visible and transmitted low battery indication
- Compatible with PowerMaster systems and PowerG receivers

GB-501 PG2 is a wireless, digital, glass-break wireless detector compatible with PowerMaster® control panels. It is designed for a wide range of residential and commercial applications where reliable glass-break detection is required. GB-501 PG2 employs an advanced, patented, acoustic pattern recognition technology that can reliably distinguish between real and false alarms.

Specifications:

Battery type:	3V, CR-123 Lithium battery
Weight (including battery):	130g (4.6oz)
Operating temperature:	0°C to 49°C (32°F to 120°F)
Operating environment:	Indoor
Dimensions:	80 x 108 x 43mm (3.1 x 4.2 x 1.7in)